

Following minima to be used by all NON-COMMERCIAL AIR TRANSPORT OPERATORS  
not applying EU-OPS or JAR-OPS AOM.

STRAIGHT-IN RWY	A	B	C	D
06 ILS	1402'(200') 700m	1402'(200') 700m	1402'(200') 800m	1402'(200') 800m
ALS out	800m	800m	900m	900m
LOC	1520'(318') 1000m	1520'(318') 1100m	1520'(318') 1200m	1520'(318') 1300m
ALS out	1000m	1300m	1400m	1500m
RNAV (GNSS)	1600'(398')	1600'(398')	1600'(398')	1600'(398')
LNAV/VNAV	1000m	1100m	1200m	1300m
ALS out	1000m	1300m	1400m	1500m
RNAV (GNSS)	1600'(398')	1600'(398')	1600'(398')	1600'(398')
LNAV	1000m	1100m	1200m	1300m
ALS out	1000m	1300m	1400m	1500m
NDB	1600'(398') 1000m	1600'(398') 1100m	1600'(398') 1200m	1600'(398') 1300m
ALS out	1000m	1300m	1400m	1500m
12 ILS	1360'(200') 700m	1360'(200') 700m	1360'(200') 800m	1360'(200') 800m
ALS out	800m	800m	900m	900m
LOC	1490'(330') 1000m	1490'(330') 1100m	1490'(330') 1200m	1490'(330') 1300m
ALS out	1000m	1300m	1400m	1500m
RNAV (GNSS)	1490'(330')	1490'(330')	1490'(330')	1490'(330')
LNAV/VNAV	1000m	1100m	1200m	1300m
ALS out	1000m	1300m	1400m	1500m
RNAV (GNSS)	1550'(390')	1550'(390')	1550'(390')	1550'(390')
LNAV	1000m	1100m	1200m	1300m
ALS out	1000m	1300m	1400m	1500m
VOR with D5.0	1530'(370') 1000m	1530'(370') 1100m	1530'(370') 1200m	1530'(370') 1300m
ALS out	1000m	1300m	1400m	1500m
VOR w/o D5.0	1820'(660') 1000m	1820'(660') 1100m	1820'(660') 1200m	1820'(660') 1300m
ALS out	1000m	1300m	1400m	1500m
24 CAT 3B ILS	approved	approved	approved	approved
CAT 3A ILS	RA50' R200m	RA50' R200m	RA50' R200m	RA50' R200m
CAT 2 ILS	1258'(100') RA101' R300m	1258'(100') RA101' R300m	1258'(100') RA101' R300m	1260'(102') RA104' R300m
ILS	1358'(200') R400m/V500m	1358'(200') R400m/V500m	1358'(200') R500m/V600m	1358'(200') R500m/V600m
CL out	R500m/V600m	R500m/V600m	R600m/V700m	R600m/V700m
ALS out	800m	800m	900m	900m
LOC	1450'(292') R700m/V800m	1450'(292') R800m/V900m	1450'(292') R800m/V900m	1450'(292') R1000m/V1200m
ALS out	1000m	1300m	1400m	1500m