

ADDITIONAL RUNWAY INFORMATION						
RWY		USABLE LENGTHS		TAKE-OFF	WIDTH	
		LANDING	BEYOND			
		Threshold	Glide Slope			
06	HIRL (60m) HIALS PAPI-L (2.98°) HSTIL-L		10,958' 3340m	③	148' 45m	
24	HIRL (60m) CL (15m) ALSF-II TDZ ① REIL ② RVR		11,040' 3365m			
① PAPI-L (2.99°)						
② HSTIL-D						
③ TAKE-OFF RUN AVAILABLE						
RWY 06:		RWY 24:				
From rwy head 12,188' (3715m)		From rwy head 12,188' (3715m)				
twy E int 10,039' (3060m)		twy B int 8350' (2545m)				
twy D int 7382' (2250m)		twy L int 5692' (1735m)				
12	HIRL (60m) HIALS PAPI-L (3.00°) RVR		9697' 2956m	④	148' 45m	
30	HIRL (60m) HIALS SFL PAPI-L (2.98°) RVR		9442' 2878m			
④ TAKE-OFF RUN AVAILABLE						
RWY 12:		RWY 30:				
From rwy head 10,663' (3250m)		From rwy head 10,663' (3250m)				
twy D int 9055' (2760m)		twy R int 8448' (2575m)				
twy F int 8284' (2525m)		twy P int 5807' (1770m)				
twy G int 7300' (2225m)						

**Standard****TAKE-OFF ①**

	LVP must be in force				RCLM (DAY only) or RL	NIL (DAY only)
	Approved Operators HIRL, CL & mult. RVR req	RL, CL & mult. RVR req	RL & CL	RCLM (DAY only) or RL		
A					400m	500m
B	125m	150m	200m	250m		
C						
D	150m	200m	250m	300m		

① Operators applying U.S. Ops Specs: CL required below 300m; approved HUD required below 150m.