



PRAGUE Radar
120.52Apt Elev
1247'Trans level: By ATC Trans alt: 5000'
Contact PRAGUE Radar immediately after take-off.

DOBEN TWO ALFA (DOBEN 2A) [DOBE2A]
DOBEN TWO DELTA (DOBEN 2D) [DOBE2D]
ONLY FOR PROPELLER DRIVER AIRCRAFT
DOBEN TWO ECHO (DOBEN 2E) [DOBE2E]
RWYS 24, 06 RNAV DEPARTURES
P-RNAV REQUIRED

SPEED RESTRICTION
JET: MAX 250 KT below FL100
PROP: MAX 180 KT below FL100
Unless otherwise instructed by ATC.



These SIDs require a minimum climb gradient
of
5% up to 3200' due to noise abatement.

Gnd speed-KT	75	100	150	200	250	300
5% V/V(fpm)	380	506	760	1013	1266	1519

Initial climb clearance **5000'**

SID	RWY	ROUTING
DOBEN 2A	24	242° track to PR402, turn LEFT, 225° track to DOBEN.
DOBEN 2D	06	062° track to PR619, turn LEFT, 324° track to PR621, turn LEFT, 242° track to ESINU, turn LEFT, 188° track to DOBEN.
DOBEN 2E		062° track to PR631, turn LEFT, 324° track to PR632, turn LEFT, 242° track to ESINU, turn LEFT, 188° track to DOBEN.

